



Ø27.5 mm

# **VALVE HEAD 4KAI TYPE N EPDM**

ART. NO. 440044E

#### **GENERAL**



The KEOFITT 4KAI Sampling Valve is our low cost sterilizable sampling valve for less demanding applications. Replaces non-hygienic sampling cocks. More than 20 different configurations available.



The sampling valve can be used for any process sampling for chemical and/or physical analysis.



Cleaning/sterilizing: Between batches: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media. Between samples: Valve in its normal closed position: cleanable by CIP as "Between batches" or the valve may be sterilized by means of steam SIP or chemical SIP using a procedure appropriate to the actual circumstances. For further advice, please contact Keofitt.

Autoclavable.



Designed for sampling of liquids with a viscosity of up to approx. 100 cP containing no particles larger than  $\emptyset$ 1.5 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).

### **FEATURES**



Installation: Threaded socket connection M18x1.5



Operation: Pneumatically operated / Lever handle (#600170)



Membrane: EPDM (#400052)

Festo Fitting QSML-M5-4

#### **CERTIFICATION\***

- · EU EC 1935/2004 · EU EC 2023/2006 · DK No. 1248 10/2018 · 3-A Certificate · ATEX 2014/34/EU
- · PED 2014/68/EU · FDA CFR 21 §177.2600 · USP Class VI · Keofitt DoC

# **TECHNICAL DATA**

# **Material (process contact)**

· Membrane EPDM, BLACK (#400052)

#### **Material (without process contact)**

Steel parts
 Lever handle
 AISI 304 (1.4307)
 AISI 316L (1.4404)

## Membrane

· Article EPDM, BLACK (#400052)

· Certification\* · EU EC 1935/2004 · EU EC 2023/2006

· DK No. 1248 10/2018 · FDA CFR 21 §177.2600 · USP Class VI

 $\cdot \, \mathsf{REACH} \cdot \mathsf{RoHS} \cdot \mathsf{ADI} \, \mathsf{Free} \cdot \mathsf{Keofitt} \, \mathsf{DoC}$ 

#### **Pressure & Temperature**

Pressure 0 - 6 bar / 0 - 87 psi
 Temperature 1 - 130°C / 34 - 266°F
 Air supply 5 - 7 bar / 73 - 102 psi

# **Net Weight**

· kg/lbs 0.362 kg/0.797 lbs

#### **Spareparts**

774444EPDM PARTS FOR 4KAI/BASIX HEAD N EPDM





