



VALVE HEAD W9 TYPE B PTFE

ART. NO. 855547

GENERAL



The KEOFITT CLASSIC W9 Sampling Valve is the original and leading sterilizable sampling valve in the world. Used in all industries for decades. More than 320 standard valve configurations. Unique serial no. for each valve*.



The sampling valve can be used for any process sampling for microbiological, chemical and/or physical analysis.



Cleaning/sterilizing: Between batches: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media. Between samples: Valve in its normal closed position: cleanable by CIP as "Between batches" or the valve may be sterilized by means of steam SIP or chemical SIP using a procedure appropriate to the actual circumstances. For further advice, please contact Keofitt.

Not recommended for autoclave due to plastic parts.



Designed for sampling of liquids with a viscosity of up to approx. 1.000 cP containing no particles larger than Ø3 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).

FEATURES



Installation: Threaded socket connection M22x1.5



Operation: Turn knob - no spring (opens counterclockwise)



Membrane: PTFE (#850055)

CERTIFICATION*

- · EU EC 1935/2004 · EU EC 2023/2006 · EU EC 10/2011 · DK No. 1248 10/2018 · ATEX 2014/34/EU
- · PED 2014/68/EU · FDA CFR 21 §177.1550 · USP Class VI · Keofitt DoC

TECHNICAL DATA

Material (process contact)

· Membrane PTFE, WHITE (#850055)

Material (without process contact)

· Steel parts AISI 303 (1.4305) / AISI 316L (1.4404)

· Knob PA6 (Black)

Membrane

· Article PTFE, WHITE (#850055)

· Certification* · EU EC 1935/2004 · EU EC 2023/2006 · EU EC 10/2011

· DK No. 1248 10/2018 · FDA CFR 21 §177.1550 · USP Class VI

· ADI Free · Keofitt DoC

Pressure & Temperature

 \cdot Pressure 0 - 12 bar / 0 - 174 psi \cdot Temperature $1 - 150^{\circ}\text{C} / 34 - 266^{\circ}\text{F}$

· Air supply _


Net Weight

· kg/lbs 0.236 kg/0.521 lbs

Spareparts

778541 PARTS FOR W9 HEAD 855541/42/43/47









KEOFITT CLASSIC W9 SAMPLING VALVE - BODIES

KE	M9 BODIES						ON B
OFI			HOSEPIECE	түз" тві-сілмр	CLIXAIM GASHHT	T\5, METDING ENDS	ON REQUEST ONLY
TT CLASSIC		TANK WELDING Ø28	950001	900088	O THE STOOM	### ##################################	ONLY!
KEOFITT CLASSIC W9 SAMPLING VALVE - BODIES		PIPE WELDING 1"	C 1100SB	930010	SEGOOSE STORES	\$50028	
	WELDING BODIES	PIPE WELDING NW25	P10058	15 an to 1 40	STOOSE	¹⁵ anba, 40	-34-
	•	IN-LINE VERTICAL	BS0027	isanbajuo	2501160160	sanbar uo	
		IN-LINE HORIZONTAL	E80028	isanba _{l UO}	25anbas uo	^{IS} anba _J UD	×
							1
		VARIVENT Ø50	0000sa	850020	ISAN BAJUO	Isanbar uo	\(\bar{A} \)
		VARIVENT Ø68	0000sa	850013	15011601 W	^{ISƏNDƏJ} UQ	
	E	MINI CLAMP	SE0038	850039	25anbas uo	sanbar uo	
	ON BODIES	CLAMP 1" & 1½"	850021	85022	C	ISANDAJ UO	.25.
		CLAMP 2"	O(***)	850028	150ntos UO	ISANDAL UN	
		CLAMP 3"	930008	1501/bajuo	15011 to	ISANDAJ UO	
		TREAD	M28X1.5 850031 850031 DIN 11851 DN 650040		BS0037 M28XLS		

OI OI OI OI