







VALVE HEAD W25 TYPE N PTFE




ART. NO. 875544

GENERAL

-  The KEOFITT CLASSIC W25 Sampling Valve is the largest KEOFITT sterilizable sampling valve. Designed for very high viscosity sampling. Unique serial no. for each valve*.
-  The sampling valve can be used for any process sampling for microbiological, chemical and/or physical analysis.
-  Cleaning/sterilizing: Between batches: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media. Between samples: Valve in its normal closed position: cleanable by CIP as "Between batches" or the valve may be sterilized by means of steam SIP or chemical SIP using a procedure appropriate to the actual circumstances. For further advice, please contact Keofitt. Autoclavable.
-  Designed for sampling of liquids with a viscosity of up to approx. 250.000 cP containing no particles larger than Ø17 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).
-  Manufacturer of the DCX3/DCX4 pneumatic actuator is Definox. For further details visit www.definox.com. The actuator can be mounted with the Definox ICS control top.



FEATURES

-  Installation: Clamp connection (clamp ring included, #900187)
-  Operation: Pneumatically operated
-  Membrane: PTFE (#870055)

CERTIFICATION*

- EU EC 1935/2004 · EU EC 2023/2006 · EU EC 10/2011 · DK No. 1248 10/2018 · ATEX 2014/34/EU
- PED 2014/68/EU · FDA CFR 21 §177.1550 · USP Class VI · Keofitt DoC

TECHNICAL DATA

Material (process contact)

- Membrane PTFE, WHITE (#870055)

Material (without process contact)

- Steel parts AISI 316L (1.4404) / AISI 304 (1.4301)

Membrane

- Article PTFE, WHITE (#870055)
- Certification*
 - EU EC 1935/2004 · EU EC 2023/2006 · EU EC 10/2011
 - DK No. 1248 10/2018 · FDA CFR 21 §177.1550 · USP Class VI
 - ADI Free · Keofitt DoC

Pressure & Temperature


- Pressure 0 - 6 bar / 0 - 87 psi
- Temperature 1 - 150°C / 34 - 302°F
- Air supply 4.5 - 8 bar / 65 - 116 psi

Net Weight

- kg/lbs 3.728 kg/8.212 lbs





Spareparts

- 778747 PARTS FOR W25 HEAD 875547/44



*For further information and download please visit www.keofitt.dk

KEOFITT CLASSIC W25 SAMPLING VALVE - BODIES

W25 BODIES		WELDING BODIES		CONNECTION BODIES	
WELDING LINER	1" CLAMP	TANK WELDING	PIPE WELDING	VARIVENT Ø68	CLAMP 3"
		 8700001	 8700002	 8700009	 8700003

- 48 -

IV >

IV >

- 49 -

