

DESCRIPTION


TRAVEL : -5° to 95° adjustable
RATIO : 52 : 1
TURNS TO CLOSE : 13
WEIGHT : 32kg. (70.5lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 125$ [4.92]
(OFF CENTER) max. $\phi 254$ [10.00]
acc. ISO 5211 : F12-F14-F16-F25
BORE : min.30[1.18] max. $\phi 80$ [3.15] #60[2.36]

TORQUE

max.OUTPUT : 5500 Nm (48679 lbf.in.)
max.INPUT : 289 Nm (2562 lbf.in.)
M.A. : 19 $\pm 15\%$




Dimensions in MM [inch]

rotork gears

Nijverheidstraat 25
7581 PV Losser
The Netherlands

GEARBOX AB 1950 N

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : Y.B

Date : 21-03-03

Dwg Nr.: D06N-001

Rev.: 06

Contents Subject to change without notice.