

DESCRIPTION


Travel : -5° to 95° adjustment
Ratio : 38 : 1
Turns to Close : 9.5
Weight : 14 Kg. (31 Lb) Excl. Handwheel

MOUNTINGHOLES

Bolt Circle : Min. $\phi 102$ [4.02]
(Off Center) Max. $\phi 165$ [6.5]
Acc. ISO 5211 : F10 - F12 - F14 - F16
Bore: Min. $\phi 16$ [0.63] - Max. $\phi 60$ [2.36] # 46 [1.81]

TORQUE

Max. Output : 2000 Nm (1770 lbf. in.)
Max. Input : 152 Nm (134 lbf. in.)
M.A. : 13.2 \pm 15%



rotork gears

Nijverheidstraat 25
7581 PV Loosdrecht
The Netherlands

GEARBOX AB 880N

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H. Date : 13-03-2002
Dwg Nr.: D04N-001 Rev.: 08

Contents Subject to change without notice.