

NEEDLE-VALVES PN 400

The valves are of forged steel construction


MATERIAL:

Stainless steel Type 46201

Body. AISI 430F
Stem. AISI 420
Packing. Graphite
Handwheel. Steelplate


Stainless steel Type 46202

Body. AISI 316L
Stem. AISI 329
Packing. Graphite
Handwheel. Steelplate



Pressure	400	160	125	20	bar
Temp	20	125	200	300	C°

Tested for 600 bar

	Size		K	d	L	D	H max	Weight kg	Kv. values
	DN	in							
	6	1/8	12	4	60	65	85	0,42	0,30
	8	1/4	14	5	60	65	85	0,40	0,42
	10	3/8	15	5	60	65	85	0,38	0,48
	15	1/2	16	5	60	65	85	0,34	0,54
	20	3/4	18	8	70	85	100	0,90	1,20
	25	1	20	10	78	100	110	1,05	1,45

- The valve can be supplied with locked boxnut.
- **Connections:** Type 46201, BSP female and male threads, NPT.
Type 46202, BSP female and male threads, NPT, socket or butt weld.
- These valves are suitable for steam, oil and gas. They are also available for a wide range of acid and alkaline fluids in chemical and processing industries.

Rubens
VERKSTAD AB

BOX 103, SE-280 60 BROBY • PHONE +46 44 401 78 • FAX +46 44 408 51